

TOWN OF FARMINGTON, NH
DEPARTMENT OF PUBLIC WORKS
14 BALDWIN WAY
PHONE: (603) 755-4884 FAX: (603) 755-4584

LOGGING, CONSTRUCTION OR FARM ACCESS PERMIT

Map and Lot:	
Public/Private Road to Driveway:	Length of Driveway:
Name of Property Owner(s):	Telephone:
Mailing address of Property Owner(s):	
Email address of Property Owner(s):	
Please specify how you would like your approval sent to you: ☐ Email ☐ US Mail	
Name of Contractor:	Telephone:
Are any State or Federal approval permits required? If so, please attach. ☐ Yes ☐ No	
Upon approval of the location of the entrance approach, Applicant and Property Owner agree to the following: 1. The grade of the approach at the location agreed upon is to be such as will permit a safe and controlled approach to the highway at all seasons, and so that NO WATER WILL DISCHARGE FROM THE APPROACH ONTO THE SURFACE OF THE HIGHWAY. 2. Property Owner shall be responsible for all maintenance associated with drainage culverts, and shall keep the culvert clean and free of debris at all times. In the event that the Property Owner fails to maintain free-flow through culvert(s), the Property Owner will be billed for costs incurred by the Town for Public Works crews having to restore flow. 3. Such drainage structures as are necessary to maintain existing highway drainage are to be furnished by the Property Owner, and their design and installation is subject to approval by the Director of Public Works in accordance with the Town of Farmington specifications. Owner understands that a Certificate of Occupancy (CO) will not be issued until such drainage structures are approved by the Director of Public Works, or for an existing property with an existing CO, may have the existing CO suspended until such drainage structures are approved by the Director of Public Works. A. Minimum diameter of culverts shall be 12 inches; larger sizes may be required on a case-by-case basis at the sole discretion of the Director of Public Works. B. Minimum length of culvert shall be 30 feet, or as required on a case-by-case basis at the sole discretion of the Director of Public Works. C. Minimum depth of cover over the culvert shall be at least equal to the diameter of the culvert (e.g. a 12-inch diameter culvert requires 12 inches of soil covering it). D. Durable headers of flat rock or precast concrete shall be installed at each end of the culvert. E. Approved types of culvert: i. ADS stiff-ribbed HDPE with smooth wall inside ii. Reinforced concrete iii. Corrugated F. Temporary culverts shall be removed promptly and natural drainage restored.	

Any alterations of the above proposed permit must have written approval of the Director of Public Works.

Signature of Owner

Date

Permission to construct an entrance approach at the location agreed upon is hereby granted:

Director of Public Works

Date